


## 28028 BRAVO DRIVER 50W

LED power supply unit

5905339280282



### GENERAL DATA:

**Colour:** white

**Place of application:** Indoors

**Possibility of installation on a normally flammable surface:** yes

**Compatible with a dimmer:** no

**Length [mm]:** 142

**Width [mm]:** 44

**Height [mm]:** 31

### TECHNICAL DATA:

**Rated voltage [V]:** 220-240 AC

**Rated current [A]:** 0,3

**Rated frequency [Hz]:** 50

**$\lambda$ :** 0,95

**Maximum power [W]:** 50

**Class of protection against electric shock:** II

**Material:** plastic

**Connection type:** Terminal block

**Range of sections of wires used [mm<sup>2</sup>]:** 0,75÷1

**Supply-cord type:** direct current

**Overload protection:** yes

**Oversupply protection:** yes

**Thermal protection:** 110°C

**Short-circuit protection:** yes

**Maximum temperature Ta [°C]:** 25

**Input voltage - PRI [V]:** 220-240

**Output voltage - SEC [V]:** 36-52

**Output current - sec [ma]:** 950

**IP class:** 20

**Tc [°C]:** 75

### LOGISTIC DATA:

**Unit of measurement:** unit

**Packaging method:** 6

**Number of units in the secondary packaging:** 6

**Number of units in the packaging:** 60

**Net unit weight [g]:** 136

**Grammage [g]:** 171

**Length of a unit pack [cm]:** 15

**Width of a unit pack [cm]:** 5.5

**Height of a unit pack [cm]:** 3.5

**Weight of a cardboard box [kg]:** 10.26

**Width of a cardboard box [cm]:** 38

**Height of a cardboard box [cm]:** 20

**Length of a cardboard box [cm]:** 39



## 28028 BRAVO DRIVER 50W

LED power supply unit

**Volume of a cardboard box [m<sup>3</sup>]: 0.02964**