

PRODUCT-DETAILS

CAL4-11

CAL4-11 Auxiliary Contact Block



General Information

Extended Product Type	CAL4-11
Product ID	1SBN010120R1011
EAN	3471523130043
Catalog Description	CAL4-11 Auxiliary Contact Block
Long Description	CAL4-11 is a 2-pole side mounted auxiliary contact block equipped with screw terminals and can be fitted on AF(C)09(Z)(B)...96 contactors and NF(C)(Z)(B) contactor relays. CAL4 auxiliary contact block can be clipped onto the right- and/or left-hand side of the contactors or the contactor relays and bears the corresponding function marking. CAL4-11 is available with 1 N.O. and 1 N.C. instantaneous contacts for standard industrial environments.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85389099
Product Main Type	Accessories for Block Contactors

Popular Downloads

Instructions and Manuals	1SBC101041M6801
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	12 mm
Product Net Depth / Length	60 mm
Product Net Height	69.4 mm
Product Net Weight	0.04 kg

Technical

Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Rigid Solid 1/2x 1 ... 2.5 mm ² Rigid Stranded 1/2x 1 ... 2.5 mm ²
Maximum Electrical Switching Frequency	(AC-15) 1200 cycles per hour (DC-13) 900 cycles per hour
Maximum Mechanical Switching Frequency	3600 cycles per hour
Mounted Auxiliary Contacts	1 NO, 1 NC
Mounting Type	Side Mounting
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Number of Poles	2
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Rated Insulation Voltage (U _i)	acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
Rated Operational Current AC-15 (I _ø)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (400 / 440 V) 3 A
Rated Operational Current DC-13 (I _ø)	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.27 A / 60 W (250 V) 0.27 A / 68 W (400 V) 0.15 A / 60 W (500 V) 0.13 A / 65 W (600 V) 0.1 A / 60 W
Rated Operational Voltage	Auxiliary Circuit 690 V
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 0.1 s 140 A for 1 s 100 A
Standards	IEC/EN 60947-5-1, UL 60947-5-1, CSA C22.2 No. 60947-5-1-14
Suitable For	AF09 AF09Z AF12 AF12Z AF16 AF16Z AF26 AF26Z AF30 AF30Z AF38 AF38Z AF40 AF52 AF65

- AF80
- AF96
- AFC09
- AFC12
- AFC16
- AFC26
- AFC30
- AFC38
- AFS09
- AFS12
- AFS16
- AFS26
- AFS30
- AFS38
- AFS40
- AFS52
- AFS65
- AFS80
- AFS96
- AF09B
- AF09ZB
- AF12B
- AF12ZB
- AF16B
- AF16ZB
- AF26B
- AF26ZB
- AF30B
- AF30ZB
- AF38B
- AF38ZB
- NF22E
- NFZ22E
- NF31E
- NFZ31E
- NF40E
- NFZ40E
- NF44E
- NFZ44E
- NF53E
- NFZ53E
- NF62E
- NFZ62E
- NF71E
- NFZ71E
- NF80E
- NFZ80E
- NF33/11
- NF51/11
- NFC22E
- NFC31E
- NFC40E
- NFC44E
- NFC53E
- NFC62E
- NFC71E
- NFC80E
- NFC33/11
- NFC51/11
- NFZB22E
- NFB22E
- NFZB31E
- NFB31E
- NFZB40E
- NFB40E
- NFZB44E
- NFB44E
- NFZB62E
- NFB62E
- NFZB80E
- NFB80E

Terminal Type	Screw Terminals
Tightening Torque	Auxiliary Circuit 1.2 N·m
Wire Stripping Length	Auxiliary Circuit 10 mm

Technical UL/CSA

Connecting Capacity	Rigid Solid 1/2x 18-14 AWG
---------------------	----------------------------

Auxiliary Circuit UL/CSA	Rigid Stranded 1/2x 18-14 AWG
Pilot Duty UL/CSA	A600 Q600
Tightening Torque UL/CSA	Auxiliary Circuit 11 in-lb

Environmental

Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-5-1, $\Theta = 40\text{ }^{\circ}\text{C}$ 16 A
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
RoHS Information	2CMT2021-006277
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations (Document Number)

ABS Certificate	ABS_20-2060694-PDA
BV Certificate	BV_2634H24900C0
CB Certificate	CB_SE-93052A1
CQC Certificate	CQC2011010304496319 CQC2019010304264779
Declaration of Conformity - CCC	2020980304001258 2020980304001053
Declaration of Conformity - CE	1SBD250007U1000
Declaration of Conformity - UKCA	1SBD250038U1000
DNV Certificate	DNV-GL_TAE00001BV-3
DNV GL Certificate	DNV-GL_TAE00001BV-3
EAC Certificate	EAC_RU C-FR ME77 B03391
Environmental Information	1SBD250145E1000
GL Certificate	DNV-GL_TAE00001BV-3
GOST Certificate	GOST_POCCFR.ME77.B07175.pdf
Instructions and Manuals	1SBC101041M6801
LR Certificate	LRS_1300087E1
REACH Declaration	2CMT2021-006202
RINA Certificate	RINA_ELE084013XG
RMRS Certificate	RMRS_1802703280
RoHS Information	2CMT2021-006277
UL Certificate	UL-US-L252354-131-82119002-6 UL-CA-L252354-331-82119002-5
UL Listing Card	UL_E252354

Container Information

Package Level 1 Units	bag 1 piece
Package Level 1 Width	125 mm
Package Level 1 Depth / Length	125 mm
Package Level 1 Height	20 mm
Package Level 1 Gross Weight	0.04 kg
Package Level 1 EAN	3471523130043

Package Level 2 Units	box 300 piece
Package Level 2 Gross Weight	12 kg
Package Level 3 Units	5400 piece

Classifications

eClass	V11.0 : 27371302
E-Number (Finland)	3706506
E-Number (Sweden)	3211435
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
ETIM 8	EC000041 - Auxiliary contact block
ETIM 9	EC000041 - Auxiliary contact block
IDEA Granular Category Code (IGCC)	4743 >> Auxiliary contact block
Object Classification Code	K
UNSPSC	39121522

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors Accessories

