

PRODUCT-DETAILS

CC5-01

CC5-01 Auxiliary Contact Block



General Information

Extended Product Type	CC5-01
Product ID	1SBN010011R1001
EAN	3471522121035
Catalog Description	CC5-01 Auxiliary Contact Block
Long Description	CC5-01 Auxiliary Contact Block

Ordering

Minimum Order Quantity	10 piece
Customs Tariff Number	85389099
Product Main Type	Accessories for Block Contactors

Popular Downloads

Data Sheet, Technical Information	1SBC100122C0202_Ch04
Instructions and Manuals	1SBC101012M5501
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	11 mm
-------------------	-------

Product Net Depth / Length	32.5 mm
Product Net Height	47 mm
Product Net Weight	0.014 kg

Technical

Maximum Electrical Switching Frequency	1200 cycles per hour
Maximum Mechanical Switching Frequency	3600 cycles per hour
Mechanical Durability	10 million 3 million
Minimum Switching Capacity	A9 ... A75 17 / 5 VLT4K A95 ... A110 24 / 50 VLT4K
Mounting Position	Front face
Mounting Type	Front mounting
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	0
Number of Poles	1
Power Loss	at Rated Operating Conditions per Pole 0.1 W
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz
Rated Insulation Voltage (U _i)	acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
Rated Operational Current AC-15 (I _θ)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (380 / 400 V) 3 A
Rated Operational Current DC-13 (I _θ)	(24 V) 6 / 144 A (48 V) 2.8 / 134 A (72 V) 1 / 72 A (125 V) 0.55 / 69 A (250 V) 0.3 / 75 A
Rated Operational Voltage	Auxiliary Circuit 690 V
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 0.1 s 140 A for 1 s 100 A
Remarks	100
Short-Circuit Protective Devices	Auxiliary Circuit - gG Type Fuses 10 A
Suitable For	AF45 AF50 AF63 AF75 A9 A12 A16 A26 A30 A40 A45 A50 A63 A75 A95 A110 AL9 AL9Z AL12 AL12Z AL16 AL16Z AL26 AL30 AL40 AE45 AE50 AE63 AE75

	TAL9
	TAL12
	TAL16
	TAL26
	TAL30
	TAL40
	TAE45
	TAE50
	TAE75
	GA75
	GAE75
	UA16
	UA26
	UA30
	UA50
	UA63
	UA75
	UA95
	UA110
	UA16RA
	UA26RA
	UA30RA
	UA50RA
	UA63RA
	UA75RA
	UA95RA
	UA110RA
	UAF75RA
	UAF95RA
	UAF110RA
	N22E
	N31E
	N40E
	NL22E
	NLZ22E
	NL31E
	NLZ31E
	NL40E
	NLZ40E
	TNL22E
	TNL31E
	TNL40E
Terminal Type	Screw Terminals

Technical UL/CSA

Pilot Duty UL/CSA	A600
	Q300

Environmental

Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
RoHS Information	2CMT2021-006277
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SBD250809U1000
Declaration of Conformity - UKCA	1SBD250826U1000
EAC Certificate	EAC_RU C-FR ME77 B03391
Environmental Information	1SBD250198E1000
GOST Certificate	GOST_POCCFRME77B07175
Instructions and Manuals	1SBC101012M5501
REACH Declaration	2CMT2021-006202
RINA Certificate	RINA_ELE172319XG001
RoHS Information	2CMT2021-006277
UL Certificate	UL 071301E48139

Container Information	
Package Level 1 Units	box 10 piece
Package Level 1 Width	65 mm
Package Level 1 Depth / Length	129.5 mm
Package Level 1 Height	40 mm
Package Level 1 Gross Weight	0.14 kg
Package Level 1 EAN	3471522121035
Package Level 2 Units	box 270 piece
Package Level 2 Width	300 mm
Package Level 2 Depth / Length	245 mm
Package Level 2 Height	308 mm
Package Level 2 Gross Weight	3.78 kg
Package Level 3 Units	9720 piece

Classifications	
eClass	V11.0 : 27371302
E-Number (Finland)	3709236
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
ETIM 8	EC000041 - Auxiliary contact block
ETIM 9	EC000041 - Auxiliary contact block
Object Classification Code	K
UNSPSC	39120000

Categories
Low Voltage Products and Systems → Control Products → Contactors → Block Contactors Accessories

