

PRODUCT-DETAILS

CM-MSS.13S

CM-MSS.13S Therm. motor protec. relay 1c/o,
110-130VAC/220-240VAC



General Information

Extended Product Type	CM-MSS.13S
Product ID	1SVR730700R2100
EAN	4013614496707
Catalog Description	CM-MSS.13S Therm. motor protec. relay 1c/o, 110-130VAC/220-240VAC
Long Description	<p>The CM-MSS.13S belongs to the CM-MSS thermistor motor protection relay range. It operates with a rated control supply voltage of 110-130 V AC and 220-240 V AC and has a 1 c/o (SPDT) output with contacts rated at 250 V / 4 A. It features one sensor circuit to monitor PTC temperature sensors and works according to the closed-circuit principle. The relay will be reset automatically after the failure has been removed. A sealable transparent cover for protection against unauthorized changes is available as accessory. The device offers screw connection technology with double-chamber cage connection terminals.</p>

Ordering

EAN 4013614496707
Minimum Order Quantity 1 piece
Customs Tariff Number 85364900

Popular Downloads

Data Sheet, Technical Information	2CDC112219D0201
Instructions and Manuals	1SVC730700M1000 1SVC730700M0000
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	22.5 mm
Product Net Height	85.6 mm
Product Net Depth / Length	103.7 mm
Product Net Weight	0.155 kg

Technical

Function	1 sensor circuit Auto reset
Rated Control Supply Voltage (U_s)	110 ... 130 V AC 220 ... 240 V AC
Rated Frequency (f)	Supply Circuit 50/60 Hz
Output	1 c/o (SPDT) contact
Terminal Type	Screw Terminals
Rated Operational Current AC-12 (I_e)	(230 V) 4 A
Rated Operational Current AC-15 (I_e)	(230 V) 3 A
Rated Operational Current DC-12 (I_e)	(24 V) 4 A
Rated Operational Current DC-13 (I_e)	(24 V) 2 A
Minimum Switching Capacity	24 V 10 mA
Rated Impulse Withstand Voltage (U_{imp})	Output Circuit 1 / Output Circuit 2 4 kV Output Circuit 4 kV
Rated Insulation Voltage (U_i)	Measuring Circuit / Output Circuit 300 V Output Circuit 1 / Output Circuit 2 300 V Supply Circuit / Measuring Circuit 300 V Supply Circuit / Output Circuit 300 V
Degree of Protection	Housing IP50 Terminals IP20
Overvoltage Category	III
Pollution Degree	3
Short-Circuit Protective Devices	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
Electrical Durability	AC-12 100000 cycle
Mechanical Durability	30000000 cycle
Connecting Capacity	Flexible 1x 0.5 ... 2.5 mm ² Flexible 2x 0.5 ... 1.5 mm ² Rigid 1x 0.5 ... 4 mm ² Rigid 2x 0.5 ... 2.5 mm ²
Tightening Torque	0.6 ... 0.8 N·m Auxiliary Circuit 1 ... 1.2 N·m Main Circuit 2.5 ... 2.7 N·m
Wire Stripping Length	8 mm Auxiliary Circuit 9 mm Main Circuit 12 mm
Recommended Screw Driver	Pozidriv 1 4.5 0.8 x 4
Mounting Position	1 ... 6
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Standards	CAN/CSA C22.2 No.14 IEC/EN 63000 IEC/EN 60947-5-1 IEC/EN 60947-8 UL 508

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Output Circuit 300 V AC
Contact Rating UL/CSA	(NC:) Q600 (NO:) Q600 (NC:) B600 (NO:) D300 B300
Connecting Capacity UL/CSA	Flexible 1x 18-14 AWG Flexible 2x 18-16 AWG Rigid 1x 20-12 AWG Rigid 2x 20-14 AWG
Tightening Torque UL/CSA	7.08 in-lb
Connecting Capacity Main Circuit UL/CSA	Flexible 1/2x 14-6 AWG
Connecting Capacity Auxiliary Circuit UL/CSA	Flexible 1/2x 18-12 AWG
Pilot Duty UL/CSA	B300 NC B600 NC Q600 NO D300 NO Q600
Flammability According to UL94	V-0

Environmental

Ambient Air Temperature	Operation -25 ... +60 °C Storage -40 ... +85 °C
Maximum Operating Altitude Permissible	Without Derating 2000 m
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

CB Certificate	CB_DK-40837-UL
CCC Certificate	CCC_2005010303165479
CQC Certificate	CQC2005010303165479
cULus Certificate	cULus508_20140912-E140448
Declaration of Conformity - CCC	2020980303000194
Declaration of Conformity - CE	1SVD981006
Declaration of Conformity - UKCA	1SVD981006-10
DNV GL Certificate	DNVGL_TAE00003W4
EAC Certificate	EAC_RU_C-DE.ME77.B.01825
Instructions and Manuals	1SVC730700M1000 1SVC730700M0000
RoHS Information	1SVD981006

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	97 mm
Package Level 1 Depth / Length	30 mm
Package Level 1 Height	109 mm
Package Level 1 Gross Weight	0.179 kg
Package Level 1 EAN	4013614496707

Classifications

Object Classification Code	B
ETIM 7	EC002568 - Relay for thermistor protection (PTC)
ETIM 8	EC002568 - Relay for thermistor protection (PTC)
ETIM 9	EC002568 - Relay for thermistor protection (PTC)
eClass	V11.0 : 27371503
UNSPSC	39122331
E-Number (Finland)	2712397
E-Number (Sweden)	3860720

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Thermistor Motor Protection Relays

